



**특 징(Feature)**

- 파이롯트압력에 의해 조작되어지는 밸브이다.
- Pilot operated valve is the valve worked by pilot pressure.

**사 양(Specifications)**

Model No.	KP-G04,06,10
규격 Nom. Dia.	04(1/3),06(3/4), 10(1 1/4)
최고사용압력 Allowable operating pressure Max . pressure	210kgf/cm2 (320kgf/cm2)
파이롯트 압력 Pilot Pressure	4.5kgf/cm2~210Kgf/cm2
허용배압 Permissible back pressure	210Kgf/cm2 (External Drain type)
중량 Weight	KP-G06(12.5Kg), KP-G10(45Kg)

**스풀형식(spool model list)**

Nomenclature	KS symbol	Nomenclature	KS symbol
JP-G***-2C		JP-G***-2B	
JP-G***-3C		JP-G***-3B	
JP-G***-33C		JP-G***-33B	
JP-G***-4C		JP-G***-4B	
JP-G***-44C			
JP-G***-5C		JP-G***-2N	
JP-G***-6C		JP-G***-3N	
JP-G***-66C		JP-G***-33N	
JP-G***-7C		JP-G***-4N	
JP-G***-8C			
JP-G***-9C		JP-G***-27C-***	